Make every second count with high-performance OCT.





www.zeiss.com/cirrus6000



Seeing beyond

High-Performance OCT Advance your fast-paced practice

CIRRUS[®] 6000, the next-generation OCT from ZEISS, delivers high-speed image capture with HD imaging detail and a wider field of view, so you can make more informed decisions and spend more time with your patients.

Performance OCT

Faster imaging with greater detail, at 100,000 scans per second, for improved patient care.

Proven analytics

Comprehensive, clinicallyvalidated tools to diagnose and manage a range of conditions.

Patient-first design

Seamless transfer of raw patient data from previous generations of CIRRUS for continuity of patient care.





The power of 100,000 scans per second

Faster imaging:

Reduce chair time and speed up your practice.

- 270% faster OCT scans and 43% faster OCTA scans.*
- OCT cube scans in as little as 0.4 seconds.
- High-speed imaging in combination with FastTrac[™] eye tracking technology reduces the chance of motion artifacts such as those caused by blinks and saccades.

Greater detail:

View more in seconds and dig deeper with high-definition imaging.

- 12×12 mm single-shot OCTA cube scan in addition to 8×8, 6×6 and 3×3 mm scans.
- High-Definition AngioPlex scans (8×8 and 6×6 mm) for even greater microvascular detail without limiting the field of view.
- 2.9 mm scan depth.

^{*} Compared to prior generations of CIRRUS.



"The CIRRUS 6000 is all about its speed. With **increased speed** comes greatly **improved resolution** and detail on cube, raster and OCTA scans, and the new faster CIRRUS enables me to incorporate these more reliable scans into my daily workflow and make **important treatment decisions** for my patients."

Theodore Leng, MD, FACS, Byers Eye Institute at Stanford, United States



12×12 mm single-shot OCTA of branch retinal vein occlusion (BRVO). Image courtesy of Jesse Jung, MD, East Bay Retina, United States



12 mm HD 1 Line Raster 100x averaged. Image courtesy of Theodore Leng, MD, Byers Eye Institute, United States

Performance OCT faster, wider, with a new level of detail

ZEISS CIRRUS 6000 empowers clinicians with a larger field of view in a single scan, and captures high-definition OCT/OCTA scans that reveal finer details of the retinal microvasculature – all of which provides more insight into the patient's condition in less time.



8×8 mm HD AngioPlex OCTA of BRVO. Image courtesy of Roger Goldberg, MD, Bay Area Retina Associates, United States



3x3 mm AngioPlex OCTA of proliferative diabetic retinopathy (PDR). *Image courtesy of Roger Goldberg, MD, Bay Area Retina Associates, United States*



6×6 mm HD AngioPlex OCTA of non-proliferative diabetic retinopathy (NPDR). *Image courtesy of Roger Goldberg, MD, Bay Area Retina Associates, United States*



12 mm HD 1 Line Raster 100x averaged. Image courtesy of Theodore Leng, MD, Byers Eye Institute, United States

Proven analytics CIRRUS-powered treatment decisions

As the pioneering OCT technology, the CIRRUS platform offers clinicians extensive, clinically-validated applications for retina, glaucoma and anterior segment. The result: precise analysis, faster throughput and smarter decision-making across a wide spectrum of clinical conditions and patient types.

Retina



Macular Change Analysis

The CIRRUS data cube automatically stores and delivers each patient's historical data to provide a variety of change assessments, including macular thickness change maps that help you understand your patient's response to treatment. Because every CIRRUS cube is tracked and registered to OCT scans from prior visits using CIRRUS' FastTrac[™] Retinal Tracking Technology, you can confidently measure point-to-point changes in macular thickness.

AngioPlex Metrix OCTA Quantification





AngioPlex[®] Metrix[™] for Macula and ONH AngioPlex Metrix allows clinicians to objectively assess and track progressive eye diseases such as diabetic retinopathy and glaucoma with quantification tools such as Vessel Density, Perfusion Density, and Foveal Avascular Zone (FAZ) for the macula, and Capillary Flux Index for the optic nerve head.

Glaucoma

The CIRRUS suite of glaucoma analysis tools are designed to help you better visualize, detect, and manage all stages of glaucoma, from glaucoma suspects and mild glaucoma to severe glaucoma.

> Ganglion Cell Analysis helps identify macular glaucomatous

damage, which can be missed

with RNFL analysis alone.

CIRRUS RNFL thickness deviation maps

have been shown to be superior for detecting localized RNFL defects, compared to traditional peripapillary RNFL thickness measurements.





RNFL Thickness Analysis

RNFL Deviation Map

З

4



2

Combined GCA and RNFL Deviation Map **AutoCenter™ – ZEISS' patented algorithm** automatically identifies the optic nerve head using Bruch's Membrane Opening (BMO) in 3-dimensions for more precise measurement of the neuro-retinal rim, accounting for tilted

discs, disruptions to the RPE and other challenging pathology.

7

5 6 C

Exams

Unique to ZEISS, Guided Progression Analysis[™] (GPA[™])

Combined GCL/IPL and RNFL

thickness deviation maps

provide a comprehensive

widefield assessment.

provides both trend and event-based analyses that detect statistically significant change and quantify rate of change for key RNFL, ONH, and GCL/IPL parameters.



Baselines

Ganglion Cell Analysis

1





9 mm epithelial thickness map of keratoconus highlights localized epithelial thinning.



9 mm high-definition cornea imaging with semi-automated measurement tools for flap thickness and residual stromal bed.

Anterior Segment Premier Module

CIRRUS also enables comprehensive imaging and quantification of the anterior segment for refractive surgery planning and follow-up, corneal evaluation and glaucoma assessment.

Patient-first design Unique platform designed for the future

With ZEISS CIRRUS 6000, your patient data is never left behind. The CIRRUS platform ensures seamless transfer of raw, dynamic patient data from previous generations of the device – enabling clinicians to maintain continuity of patient care, even as OCT technology evolves over time.



Technical specifications

ZEISS CIRRUS 6000

Key Parameters

Methodology:	Spectral domain OCT		
Optical source:	Superluminescent diode (SLD), 840 nm		
A-scan depth:	2.0 - 2.9 mm (in tissue)		
Scan speed:	100,000 A-scans per second		
Min. pupil diameter:	2.0 mm		
Resolution:			
 Axial resolution 	5 μm (in tissue), 1.95 μm (digital)		
 Transverse resolution 	15 μm (in tissue)		
Refractive error adjustment:	-20D to +20D (dopters)		
Fundus Imaging:			
Methodology	Line Scanning Laser Ophthalmoscope (LSO)		
 Optical Source 	SLD 750 nm		
 Field of View (degrees) 	36×30		
Posterior Segment scans:			
OCT	Cube scan (Macula and Optic Disc)		
	HD Raster (1, 5, 21-line, cross and radial); Raster scan length 3-12 mm;		
■ OCTA	image averaging up to 100x		
	3×3, 6×6, 8×8, 12×12 mm (Macula); 4.5×4.5 mm (Optic Nerve Head);		
	14×10 mm (Montage), 14×14 mm (Montage)		
Anterior Segment scans:	Cube, HD Cornea, Pachymetry, HD Angle, Wide Angle-to-Angle,		
	Anterior Chamber, 5-Line Raster		

Analytical applications

Retina: Macular Thickness Analysis with Reference Database (Diversified and Asian) Macular Change Analysis Advanced RPE Analysis 3D Visualization En Face Analysis CIRRUS Wellness Exam	Glaucoma: Guided Progression Analysis Ganglion Cell/IPL Thickness with Reference Database (Diversified and Asian) RNFL Thickness with Reference Database (Diversified and Asian) ONH Parameters with Reference Database (Diversified and Asian) Average cup-to-disc ratio Average, Superior and Inferior RNFL Thickness CIRRUS Wellness Exam
 Anterior Segment: 9 mm Epithelial Thickness and Pachymetry Mapping HD Cornea with Cornea Caliper Tool ChamberView[™] Full Anterior Chamber Imaging for phakic IOL sizing and safety distance measurements Angle imaging and measurement tools for Glaucoma (AOD, TISA, SSA) 	AngioPlex Metrix OCT Angiography Quantification: Macular Foveal Avascular Zone Perfusion Density (ETDRS grid) Vessel Density (ETDRS grid) Optic Nerve Head Capillary Perfusion Density Capillary Flux Index AngioPlex 2-visit comparison

Instrument Specifications

Weight:	35 kg (77 lbs) (without monitor)
Dimensions (L \times W \times H):	62.2 × 42.5 × 29.2 cm (24.4 × 16.7 × 11.4 in) (without monitor)
Input Power:	
 Voltage and Mains Frequency 	230V, 100/120V, 50-60Hz
 Electrical Class 	IEC 60601-1 Class I

Computer Specifications

Monitor:	22" Widescreen HD	Resolution:	1920×1080	
Internal storage:	2 TB with 128 GB SSD	USB Ports:	8	
Input devices:		Wireless keyboard, Wirele	Wireless keyboard, Wireless mouse	
Processor:		Intel [®] Core i7 (7th Gen)	Intel® Core i7 (7th Gen)	
Operating system (Instrument):		Windows [®] 10 Enterprise	Windows® 10 Enterprise	
Supported operating systems (Review Station):		Windows [®] 10, Windows [®]	Windows [®] 10, Windows [®] 8.1, Windows [®] 7 (64 bit)	

EN_31_010_00471 CZ XI/2019 International edition: Only for sale in selected countries.





Dublin, CA 94568 USA www.zeiss.com/cirrus6000 www.zeiss.com/med/contacts



Carl Zeiss Meditec AG

Goeschwitzer Strasse 52 07745 Jena Germany www.zeiss.com/cirrus6000 www.zeiss.com/med/contacts