# **EUSION** SD-OCT & Digital Fundus Photography



**The Complete Retinal Imaging Solution** 



## **∠Fusion**<sup>™</sup> THE COMPLETE RETINAL IMAGING SOLUTION

iFusion combines the best of Spectral-Domain OCT and Fundus imaging by adding the powerful OCT capabilities of **¿Vue**<sup>•</sup> and high quality imaging from **¿Cam<sup>•</sup>** on a single, integrated, versatile platform that will add value to your practice.


### SAVE TIME & SPACE FOR PRACTICE EFFICIENCY

iFusion enhances your practice efficiency by streamlining your workflow in evaluating the patient with OCT and fundus imaging at one compact instrument.

### UPGRADE OPTIONS FOR MORE FLEXIBILITY

As your technology needs change, iFusion's modularity provides you various upgrade pathways to choose from so that you can offer the latest in OCT and fundus imaging to your patients.





High Quality Imaging | Affordable | Easy Integration

# The Fusing of OC Fundus Photography





\*For illustrative purposes only



**¿**Fusion<sup>®</sup>

SD-OCT & Digital Fundus Photography

## **¿Vue**°sd-oct

#### **SPECIFICATIONS**

iVue Scanner: OCT Image: 26,000 A-scan/second Frame Rate: 256 to 1024 A-scan/Frame Depth Resolution (in tissue) : 5.0 μm

Scan Range: Depth: 2 or 2.3mm Transverse: 2mm to 12mm

Scan Beam Wavelength:  $\lambda = 840 \pm 10$  nm

Exposure Power at pupil: 700µW to 750µW

External Image (Live IR) FOV: 13mm x 9mm

Patient Interface: Working Distance: 21.2mm for retina, 16.6 for cornea Motorized Focus Range: -15D to +10D

## Cam<sup>™</sup> Non-Mydriatic Fundus Camera SPECIFICATIONS Field Angle: 45° Image: 5.2 Million Pixels Pupil Diameter: ≥4mm Illumination During Alignment to Patient's Eye: NIR LED Flash for Retina Image Capture: White LED located inside the instrument

White LED located inside the instrument at the end of the illumination optical train, synchronized to flash with the capture function

Cornea Image: Illumination from 3 external white LED sources in steady state mode

Total Focus Diopter Adjustment Range: -35D to +30D

Z-ranging (Working Distance): ~25mm

Fixation: 6 Internal & 1 Adjustable External

Focus Adjustment: Manual

## Computer

All-In-One

#### SPECIFICATIONS

21.5" Display Windows 7<sup>®</sup> i5 Intel<sup>®</sup> Processor 4GB Memory 500GB Storage

